





### Product benefits




PVC-free



Nonwoven adhesive



For walls and ceilings



Can be re-painted several times



Breathable




Impact-resistant



No soaking




Easy to use




Covers cracks



Low paint consumption



Paste-the-wall technique



Easy to remove



Fire-retardant

### How to use



**1.** Remove old wallpaper and paint. Smooth rough base surfaces with plaster-based filler. Prime very absorbent base surfaces with solvent-free primer.



**2a.** Use with the paste-the-wall technique – no soaking. Or



**2b.** Use a pasting machine without soaking. Use nonwoven adhesive.



**3.** Hang perpendicular, with the lengths butted jointed to each other.



**4.** Place the wallpaper length free of bubbles and folds into the adhesive bed, and press with a foam rubber roller or wallpapering brush.



**5.** Use a Stanley knife and wallpapering palette knife to trim off excess material at ceilings, skirting boards or windows etc.



**6.** Trim off excess wallpaper at the corners and edges and butt joint the next length.



**7.** When dry, apply one or two coats of high-quality emulsion paint (EN 13300-compliant).



# Technical Data Sheet 10/2015

## Product Description

### ERFURT-Vlies-Rauhfaser

#### Manufacturer

ERFURT & SOHN KG • Hugo-Erfurt-Straße 1  
42399 Wuppertal • GERMANY • [www.erfurt.com](http://www.erfurt.com)

#### Raw materials/Manufacture

ERFURT-Vlies-Rauhfaser is a wallcovering consisting of several layers of paper into which the texture-forming wood fibres are firmly incorporated.

All ERFURT-Vlies-Rauhfaser designs are manufactured using the same production processes and differ only in terms of the texture-forming wood fibres. Only high-quality raw materials as well as specially selected recycling paper and cellulose textile fibres are used for production. The print dyes of the recycling paper for the covering layer are removed using the flotation de-inking technique. Any production waste can be fed back to the production process.

The water required for production is repeatedly circulated and is cleaned and purified before being returned to the environment.

#### Product data

- Roll dimensions: 15.00 m long x 0.53 m wide  
(Vlies-Rauhfaser Rustic: 10.05 m long x 0.53 m wide)
- Carton content: 12 rolls

#### Product features

- Its water vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer thickness of approximately 0.02m
- Fire rating "B-s1,d0" according to EN 13501-1 corresponds to "B1" (fire-retardant) according to DIN 4102-1
- Free of PVC, plasticisers and solvents harmful to health
- Fibreglass-free
- No heavy metal compounds or formaldehyde added
- Dimensionally stable and covers cracks
- Conforms to EN 234 (Specification for wallcoverings for subsequent decoration).
- Easy to remove after moistening with water
- Can be re-painted several times with commercially available paints
- Suitable for allergy-sufferers

## Application/Handling

### Base surface

ERFURT-Vlies-Rauhfaser can be used on all interior base surfaces suitable for wallpapering.

### Paste/Adhesive

Use nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l water) or a comparable product. Please read the adhesive manufacturer's instructions for use.

### Wallpapering

Apply the adhesive evenly to the base surface and place the cut lengths dry into the bed of adhesive (paste-the-wall technique). Alternatively, ERFURT-Vlies-Rauhfaser can also be pasted using a pasting machine, folded together and applied without soaking. Hang ERFURT-Vlies-Rauhfaser perpendicular, with the lengths butt jointed to each other. Press the widths free of bubbles using a rubber roller or a wallpapering brush. Press excess lengths at ceilings, skirtings, windows etc. into the corners with a straight edge and cut off with a Stanley knife. Ensure that the wallcovering does not overlap.

### Painting

Once dry, paint the surface of the Vlies-Rauhfaser with high-quality emulsion paint.

Special effects and techniques are also possible if required.

## Ingredients/Test results

ERFURT-Vlies-Rauhfaser consists of paper fibres, of which approx. 70% are recycled paper, polyester fibres, wood fibres and additives.

Dispose of painted ERFURT-Vlies-Rauhfaser with normal household waste.

By awarding its allergy seal the TÜV North certifies that ERFURT-Vlies-Rauhfaser has been manufactured using strict controls over allergens and pollutant materials. It is therefore also suitable for extremely sensitive people and people with allergies.

Its water vapour permeability was certified by the ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH in Aschaffenburg, Germany and conforms to DIN 52615 with Test Report 1743/32.

#### Made in Germany

ERFURT & SOHN KG  
Hugo-Erfurt-Straße 1  
D-42399 Wuppertal

Tel.: +49 202 6110 0  
Fax: +49 202 6110 89 451

E-mail: [info@erfurt.com](mailto:info@erfurt.com)  
Internet: [www.erfurt.com](http://www.erfurt.com)

Service line:  
**+49 202 6110 375**

**ERFURT**  
WÄNDE ZUM WOHLFÜHLEN