



# ERFURT-Vliesfaser MAXX

## Economy

**ERFURT**  
WÄNDE ZUM WOHLFÜHLEN

STRUKTUR- UND  
VLIESTAPETEN


### Product benefits




PVC-free



Fire-retardant



For walls and ceilings




Low paint consumption



Breathable



Impact-resistant




Covers cracks




No soaking



Nonwoven adhesive



Paste-the-wall technique



Easy to remove

### How to use



**1.** Remove old wallpaper and paint. Smooth rough base surfaces with plaster-based filler. Prime very absorbent base surfaces with solvent-free primer.



**2a.** Use with the paste-the-wall technique – no soaking. Or



**2b.** Use a pasting machine without soaking. Use nonwoven adhesive.



**3.** Hang perpendicular, with the lengths butt jointed to each other. Press the widths free of bubbles using a wallpapering brush or rubber roller.



**4.** Use a sponge roller to smooth down the wallpaper.



**5.** Use a Stanley knife and wallpapering palette knife to trim off excess material at ceilings, skirting boards or windows etc.



**6.** Trim off excess wallpaper at the corners and edges and butt joint the next length.



**7.** When dry, paint with high-quality emulsion paint in line with EN 13300 or possibly plaster or wallpaper etc.

Vliesfaser

[www.erfurt.com](http://www.erfurt.com)



# Technical Data Sheet 10/2015

## Product Description

### ERFURT-Vliesfaser MAXX Economy

#### Manufacturer

ERFURT & SOHN KG • Hugo-Erfurt-Straße 1  
42399 Wuppertal • GERMANY • [www.erfurt.com](http://www.erfurt.com)

#### Raw materials/Manufacture

ERFURT-Vliesfaser MAXX Economy is a durable wallcovering, manufactured from special cellulose and textile fibres combined with polymer binding agents in a special embossing process.

All ERFURT-Vliesfaser MAXX Economy types are manufactured using the same production processes.

#### Product data

- Roll dimensions: 12.5 m long x 0.53 m wide
- Carton content: 9 rolls

#### Product features

- Its water vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer thickness of approximately 0.02 m.
- In conjunction with mineral-based base surfaces in compliance with EN 13501-1, B-s1,d0 (fire-retardant)
- Free of PVC, plasticisers and solvents harmful to health
- Fibreglass-free
- No heavy metal compounds or formaldehyde added
- Dimensionally stable and covers cracks
- Very durable when used with corresponding paints
- Easy to remove after moistening with water
- Can be re-painted several times with commercially available paints
- Painting required
- We recommend painting to protect the surface and emphasise the embossing.

## Application/Handling

ERFURT-Vliesfaser MAXX Economy can be used on all interior base surfaces suitable for wallpapering.

### Using the paste-the-wall technique

Use nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l water) or a comparable product. Apply the adhesive evenly to the base surface and place the cut lengths dry into the bed of adhesive. Please read the adhesive manufacturer's instructions for use.

### Using a pasting machine

ERFURT-Vliesfaser MAXX Economy wallcoverings can also be pasted using a pasting machine, folded together and applied without soaking. Use nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l water) or a comparable product. Please read the adhesive manufacturer's instructions for use.

### Wallpapering

Hang ERFURT-Vliesfaser MAXX Economy perpendicular, with the lengths butt jointed to each other. Press the widths free of bubbles using a rubber roller or a wallpapering brush. Press excess lengths at ceilings, skirtings, windows etc. into the corners with a straight edge and cut off with a Stanley knife. Ensure that the wallcovering does not overlap.

### Painting

ERFURT-Vliesfaser MAXX Economy needs to be painted. High quality satin gloss or high-gloss emulsion paint is most suitable, as these highlight the textures better and are more durable compared to matt paint.

## Ingredients/Test results

Its water vapour permeability was certified by the ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH in Aschaffenburg, Germany and conforms to DIN 52615 Section 1 with Test Report 1743/37.

#### Made in Germany

ERFURT & SOHN KG  
Hugo-Erfurt-Straße 1  
D-42399 Wuppertal

Tel.: +49 202 6110 0  
Fax: +49 202 6110 89 451

E-mail: [info@erfurt.com](mailto:info@erfurt.com)  
Internet: [www.erfurt.com](http://www.erfurt.com)

Service line:  
**+49 202 6110 375**

**ERFURT**  
WÄNDE ZUM WOHLFÜHLEN